

SCOPE OF CERTIFICATION
Timber Window Scheme to BS644 & PAS24:2016

Manufacturer of Enhanced Security Windows in accordance with the Exova BM TRADA Q-Mark Scheme requirements.
(Check with Secured by Design to ensure compliance with any additional requirements).

Selectron Elektrokimya Sanayi ve Ticaret Ltd Sti

Dereboyu Cd

Sengul Sk

No: 6 34303 Halkali

Istanbul



This scope of certification supports
WGPS Certificate 026/184
ESW Certificate 031/190

The validity of this scope document should be checked against the current schedule of the Company's certification listed on the Exova BM TRADA website www.exovabmtrada.com.

Completed: **E. Watkin**

Checked: **T. Johnson**

Issue: **1**

Date: **02 March 2018**

Details: First issue of scope.

Product Name:

**Arbor Fenex 68f Window Range –
Inward Opening, Alu Clad Timber Tilt & Turn
Window**

This document remains the intellectual property of Exova BM TRADA. It shall not be made available to another person or company without the prior written permission of Exova BM TRADA.

Window Classification 'W'

Test evidence is held on file by Exova BM TRADA

Weather rating

BS6375 part 1 Exposure category **1600** (on largest specimen)


Maximum casement size

Tilt Turn (not including frame)

1012mm wide x 1512mm high

Design options

Designs shown below are diagrammatical only. Refer to minimum / maximum sizes below for clarification.



Transom and mullion joints Type A, B & C are **NOT** only allowed within window outer frames for this scope.

Type A Transoms or mullions connected only to the outer frame/ casement	Type B Transoms or mullions connecting to another transom or mullion as a 'T' joint.	Type C Transoms or mullions connecting to another transom or mullion as a 'Cruciform' joint.
---	--	--

Casement / sash

	Material/type	Dimensions (mm)	Nom. Density (Kg/m ³)
Stiles and rails	Pine	78 x 64	450
Cladding Option	Cladding (Ref: LA 776 – Uniform Aluminium) Cladding (Ref: LA 860 – Uniform Aluminium) Clip fitted onto face of timber	12 x 88 15 x 38	-
Rebate	Single Type	18	-
Drip bar	Not required	-	-
Joints	Finger jointed / Conduit	-	-
Adhesive	D4	-	-

Window frame

	Material/type	Dimensions (mm)	Nom. Density (Kg/m ³)
Stiles and rails	Pine	68 x 70	450
Cladding Option	Cladding (Ref: LA 776 – Uniform Aluminium) Clip fitted onto face of timber	12 x 88	-
Rebate	Single type	18	-
Drip bar	Not required	-	-
Joints	Finger jointed / Conduit	-	-
Adhesive	D4	-	-

Perimeter sealing details

	Make/type	Size (mm)	Location
Casement edges	None present	-	-
Frame reveal	Schlegel (Ref. QL3053 & QL3054)	8 wide	On rebate upstand into seal groove
Seal continuity	Uninterrupted by hardware	-	-

Hardware

	Make/type	Size (mm)	Fixing details (dimensions in mm)
Tilt Turn Locking System	MACO Pivot Post Ref: 52703 R/H or 52704 L/H Centre Lock Ref: 52755 Drive Gear Ref: 55443 Scissor Stay Hinge Ref: 202543 Scissor Stay Support Ref: 202534 Scissor Stay Ref: 52446 Corner Element Ref: 52936 Corner Support Ref: 57116 R/H or 57117 L/H	16 Wide	3.5 x 35 screws into frame 3.5 x 35 screws into casement
Keeps	7No. MACO Keeps (Ref. 96561) & 1No. MACO Keep (Ref. 34981) Please note 7No. keeps used on maximum size of product noted with scope	68 x 20 48 x 19	2No. 3.5 x 35 screws into frame 2No. 3.5 x 35 screws into frame
Handles	MACO (Ref. Rhapsody)	120 lever length	2No. M5 x 40 screws (Supplied with component)
Letter plate	Not Assessed	-	-

Glazing

	Make/type/size (mm)	Location (dimensions in mm)
Glass type & configuration	52 thick insulating glass unit (triple glazed) All insulating glass units used within a Q-Mark certified window must: - Be certified by an accredited Certification Body to BS EN 1279 part 2 and part 6 - When adjacent to doorsets or using non-key unlocking hardware, have at least 1 pane of laminated glass classified to BS EN 356 class P1A or higher	
Overall size	880 wide x 1380 high	-
Glazing bead	Uniform Aluminium (Ref: LA 860) 15 x 38	Externally beaded
Bead fixings	Screw fixed using 3.5 x 25mm screws @ 200mm centres	
Security Clips	Uniform Aluminium (Ref: LC 62) Fixed 80mm from corners and 200mm centres	
Glazing Tape	3mm Thick EPDM (Ref: DE34) – External	Between bead and glass IGU
	3mm Thick EPDM (Ref: DE34) – Internal	Between rebate upstand and glass